



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM171101208801  
Page: 1 of 34

## **TEST REPORT**

**Application No.:** SZEM1711012088PS  
**Applicant:** Shenzhen Dipinle Technology Co., Ltd  
**Address of Applicant:** 2/F, Block 2, GuanFeng Industrial Area, JiuWei Village, Xixiang Town, Baoan District, Shenzhen 518126, China  
**Manufacturer/ Factory:** Shenzhen Dipinle Technology Co., Ltd  
**Address of Manufacturer/ Factory:** 2/F, Block 2, GuanFeng Industrial Area, JiuWei Village, Xixiang Town, Baoan District, Shenzhen 518126, China  
**Equipment Under Test (EUT):**  
**EUT Name:** WALL CHARGER  
**Model No.:** CA-29, CA-29A, CA-29T, CA-27A Plus, CA-27T Plus ♣  
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**Trade mark:** UONIPOW  
**Standard(s) :** EN 55032:2015  
EN 61000-3-2:2014  
EN 61000-3-3:2013  
EN 55024:2010 +A1:2015  
**Date of Receipt:** 2017-12-04  
**Date of Test:** 2017-12-04 to 2017-12-05  
**Date of Issue:** 2017-12-07

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.



Jack Zhang  
EMC Laboratory Manager





The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-12-07		Original

Authorized for issue by:				
				
		Foray Chen /Project Engineer		
				
		Eric Fu /Reviewer		

## 2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	EN 55032:2015	EN 55032:2015	Class B	Pass
Radiated Emissions (30MHz-1GHz)	EN 55032:2015	EN 55032:2015	Class B	Pass
Harmonic Current Emission	EN 61000-3-2:2014	EN 61000-3-2:2014	Class A	Pass
Voltage Fluctuations and Flicker	EN 61000-3-3:2013	EN 61000-3-3:2013	Clause 5 of EN 61000-3-3	Pass

Immunity Part				
Item	Standard	Method	Requirement	Result
Electrostatic Discharge	EN 55024:2010 +A1:2015	EN 61000-4-2:2009	4kV Contact Discharge 8kV Air Discharge	Pass
Radiated Immunity (80MHz-1GHz)	EN 55024:2010 +A1:2015	EN 61000-4-3:2006 +A1:2008+A2:2010	3V/m, 80%, 1kHz Amp. Mod.	Pass
Electrical Fast Transients/Burst at Power Port	EN 55024:2010 +A1:2015	EN 61000-4-4:2012	1kV/50ns Tr/Td 5kHz Repetition Frequency	Pass
Surge at Power Port	EN 55024:2010 +A1:2015	EN 61000-4-5:2014	1.2/50µs Tr/Td 1kV Line to Line 2kV Line to Ground	Pass
Conducted Immunity at Power Port (150kHz-80MHz)	EN 55024:2010 +A1:2015	EN 61000-4-6:2014	3Vrms (emf), 80%, 1kHz Amp. Mod.	Pass
Voltage Dips and Interruptions	EN 55024:2010 +A1:2015	EN 61000-4-11:2004	0 % UT for 0.5per 0 % UT for 250per 70 % UT for 25per UT is Supply Voltage	Pass

Internal Source	Upper Frequency
Below 108MHz	1GHz
108MHz to 500MHz	2GHz
500MHz to 1GHz	5GHz
Above 1GHz	5 times the highest frequency or 6 GHz, whichever is less

### Declaration of EUT Family Grouping:

Model No.: CA-29, CA-29A, CA-29T, CA-27A Plus, CA-27T Plus

Only the model CA-29 was tested, since the electrical circuit design, PCB layout, components used and internal wiring were identical for the above models, with only difference being of case, USB and model No..



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>6</b>
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	6
4.3 MEASUREMENT UNCERTAINTY .....	6
4.4 TEST LOCATION .....	7
4.5 TEST FACILITY .....	7
4.6 DEVIATION FROM STANDARDS .....	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
4.8 MONITORING OF EUT FOR ALL IMMUNITY TEST .....	7
<b>5 EQUIPMENT LIST .....</b>	<b>8</b>
<b>6 EMISSION TEST RESULTS .....</b>	<b>11</b>
6.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz) .....	11
6.1.1 E.U.T. Operation .....	11
6.1.2 Test Setup Diagram .....	11
6.1.3 Measurement Data .....	11
6.2 RADIATED EMISSIONS (30MHz-1GHz) .....	14
6.2.1 E.U.T. Operation .....	14
6.2.2 Test Setup Diagram .....	14
6.2.3 Measurement Data .....	14
6.3 HARMONIC CURRENT EMISSION .....	17
6.4 VOLTAGE FLUCTUATIONS AND FLICKER .....	18
6.4.1 E.U.T. Operation .....	18
6.4.2 Test Setup Diagram .....	18
6.4.3 Measurement Data .....	18
<b>7 IMMUNITY TEST RESULTS .....</b>	<b>20</b>
7.1 PERFORMANCE CRITERIA DESCRIPTION IN EN 55024:2010 +A1:2015 .....	20
7.2 ELECTROSTATIC DISCHARGE .....	21
7.2.1 Test Setup Diagram .....	21
7.2.2 E.U.T. Operation .....	21
7.2.3 Test Results: .....	21
7.3 RADIATED IMMUNITY (80MHz-1GHz) .....	22
7.3.1 Test Setup Diagram .....	22
7.3.2 E.U.T. Operation .....	22
7.3.3 Test Results: .....	22
7.4 ELECTRICAL FAST TRANSIENTS/BURST AT POWER PORT .....	23
7.4.1 Test Setup Diagram .....	23
7.4.2 E.U.T. Operation .....	23
7.4.3 Test Results: .....	23
7.5 SURGE AT POWER PORT .....	24
7.5.1 Test Setup Diagram .....	24
7.5.2 E.U.T. Operation .....	24



7.5.3	Test Results:.....	24
7.6	CONDUCTED IMMUNITY AT POWER PORT (150KHz-80MHz).....	25
7.6.1	Test Setup Diagram.....	25
7.6.2	E.U.T. Operation.....	25
7.6.3	Test Results:.....	25
7.7	VOLTAGE DIPS AND INTERRUPTIONS .....	26
7.7.1	Test Setup Diagram.....	26
7.7.2	E.U.T. Operation.....	26
7.7.3	Test Results:.....	26
8	PHOTOGRAPHS.....	27
8.1	CONDUCTED EMISSIONS AT MAINS TERMINALS (150KHz-30MHz) TEST SETUP .....	27
8.2	RADIATED EMISSIONS (30MHz-1GHz) TEST SETUP.....	27
8.3	VOLTAGE FLUCTUATIONS AND FLICKER TEST SETUP .....	28
8.4	ELECTROSTATIC DISCHARGE TEST SETUP .....	28
8.5	RADIATED IMMUNITY (80MHz-1GHz) TEST SETUP.....	29
8.6	ELECTRICAL FAST TRANSIENTS/BURST AT POWER PORT TEST SETUP .....	29
8.7	SURGE AT POWER PORT TEST SETUP.....	30
8.8	CONDUCTED IMMUNITY AT POWER PORT (150KHz-80MHz) TEST SETUP .....	30
8.9	VOLTAGE DIPS AND INTERRUPTIONS TEST SETUP.....	31
8.10	EUT CONSTRUCTIONAL DETAILS (EXTERNAL AND INTERNAL PHOTOS) .....	32-34



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	Input: AC100-240V 50/60Hz Output: DC5V 3A, DC9V 2A. DC12V 1.5A
---------------	---

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Load Resistor	SGS	N/A	REF. No.SEA0600
Type- C cable	SGS	N/A	N/A

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction emission	3.0dB (150kHz to 30MHz)
2	Radiated emission	4.5dB (30MHz-1GHz)
3	Radiated Immunity	1.64dB
4	Conducted Immunity	0.96dB
5	ESD	6 %
6	EFT (Electrical Fast Transients)	5 %
7	Surge Immunity	5 %
8	Voltage Dips and Interruptions	4 %
9	Temperature test	1 °C
10	Humidity test	3%



#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

#### **4.8 Monitoring of EUT for All Immunity Test**

Visual: Monitored the light and output voltage of the EUT

Audio: None



## 5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2017-07-13	2018-07-12
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2017-04-14	2018-04-13

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2017-07-13	2018-07-12
EMI Test Receiver (9kHz-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-13
Trilog-Broadband Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2017-06-05	2018-06-04

Voltage Fluctuations and Flicker					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
AC Power Source	California Instruments	5001ix	SEM016-02	2017-04-14	2018-04-13
Power Analyzer	California Instruments	PACS-1	SEM016-01	2017-04-14	2018-04-13
Measurement Software	California Instruments	CTS 3.0 V3.2.0.6	N/A	N/A	N/A

Electrostatic Discharge					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
ESD Ground Plane	SGS(3m*3m)	N/A	SEN006-01	N/A	N/A
ESD Generator	TESEQ AG	NSG 437	SEM019-02	2017-06-08	2018-06-07





**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM171101208801

Page: 9 of 34

<b>Radiated Immunity (80MHz-1GHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Fully-Anechoic Chamber 2	Chang Zhou Zhong Shuo	854	SEM001-05	2015-05-13	2018-05-12
Measurement Software	Rohde & Schwarz	EMC32 V9.25.00	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SMB100A	SEM006-11	2017-04-14	2018-04-13
Broadband Amplifier (80MHz-1GHz)	Rohde & Schwarz	BBA150- BC250	SEM005-12	2017-09-27	2018-09-26
Broadband Amplifier (800MHz-3GHz)	Rohde & Schwarz	BBA150	EMC2092	2017-01-20	2018-01-19
Broadband Amplifier (2.5GHz-6GHz)	Rohde & Schwarz	BBA150-E60	SEM005-16	2017-07-17	2018-07-16
Power Sensor	Rohde & Schwarz	NRP-Z91	SEM009-09	2017-04-14	2018-04-13
Power Sensor	Rohde & Schwarz	NRP-Z91	SEM009-08	2017-04-14	2018-04-13
Stacked Log.-Per.- Broadband Antenna (70MHz-10GHz)	Schwarzbeck	STLP 9129	SEM003-25	N/A	N/A

<b>Electrical Fast Transients/Burst at Power Port</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Ultra Compact Simulator	EM TEST	UCS 500N7	SEM018-02	2017-07-17	2018-07-16
Measurement Software	EM TEST	IEC CONTROL V6.0.1	N/A	N/A	N/A

<b>Surge at Power Port</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Ultra Compact Simulator	EM TEST	UCS 500N7	SEM018-02	2017-07-17	2018-07-16
Measurement Software	EM TEST	IEC CONTROL V6.0.1	N/A	N/A	N/A

<b>Conducted Immunity at Power Port (150kHz-80MHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Shielding Room	AUDIX	N/A	SEM001-08	2017-05-10	2018-05-10
RF-Generator	SCHAFFNER	NSG 2070	SEM006-01	2017-09-27	2018-09-26
Coupling/Decoupling Network	SCHAFFNER	CDN M016	SEM007-03	2017-07-17	2018-07-16



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM171101208801

Page: 10 of 34

Voltage Dips and Interruptions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Ultra Compact Simulator	EM TEST	UCS 500N7	SEM018-02	2017-07-17	2018-07-16
Measurement Software	EM TEST	IEC CONTROL V6.0.1	N/A	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17

## 6 Emission Test Results

### 6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	EN 55032:2015
Test Method:	EN 55032:2015
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

#### 6.1.1 E.U.T. Operation

Operating Environment:


Temperature: 22.5 °C      Humidity: 56.2 % RH      Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case:

- a: DC5V full output mode, keep EUT working with full load.
- b: DC9V full output mode, keep EUT working with full load.
- c: DC12V full output mode, keep EUT working with full load.
- d: Idle mode.

The worst case for final test: c: DC12V full output mode, keep EUT working with full load.


#### 6.1.2 Test Setup Diagram



#### 6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

Mode:c; Line:Live Line



Site : Shielding Room


Condition: Line

Job No. : 12088PS

Test mode: c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.20	0.02	9.50	22.18	31.70	53.71	-22.01	Average
2	0.20	0.02	9.50	39.85	49.37	63.71	-14.34	QP
3	0.31	0.01	9.51	16.74	26.26	50.06	-23.80	Average
4	0.31	0.01	9.51	34.04	43.56	60.06	-16.50	QP
5	0.41	0.01	9.49	11.21	20.71	47.73	-27.02	Average
6	0.41	0.01	9.49	26.04	35.54	57.73	-22.19	QP
7	0.69	0.02	9.49	16.15	25.66	46.00	-20.34	Average
8	0.69	0.02	9.49	30.37	39.88	56.00	-16.12	QP
9	1.24	0.02	9.51	6.23	15.76	46.00	-30.24	Average
10	1.24	0.02	9.51	21.61	31.14	56.00	-24.86	QP
11	1.65	0.02	9.51	4.81	14.34	46.00	-31.66	Average
12	1.65	0.02	9.51	19.69	29.22	56.00	-26.78	QP

Mode:c; Line:Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 12088PS

Test mode: c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.02	9.59	21.24	30.85	55.16	-24.31	Average
2	0.17	0.02	9.59	37.38	46.99	65.16	-18.17	QP
3	0.21	0.02	9.57	26.78	36.37	53.40	-17.03	Average
4	0.21	0.02	9.57	39.92	49.51	63.40	-13.89	QP
5	0.31	0.01	9.58	17.76	27.35	49.97	-22.62	Average
6	0.31	0.01	9.58	35.39	44.98	59.97	-14.99	QP
7	0.51	0.01	9.60	11.54	21.15	46.00	-24.85	Average
8	0.51	0.01	9.60	29.32	38.93	56.00	-17.07	QP
9	0.69	0.02	9.62	16.31	25.95	46.00	-20.05	Average
10	0.69	0.02	9.62	32.07	41.71	56.00	-14.29	QP
11	0.81	0.02	9.61	11.59	21.22	46.00	-24.78	Average
12	0.81	0.02	9.61	31.54	41.17	56.00	-14.83	QP

## 6.2 Radiated Emissions (30MHz-1GHz)

Test Requirement:	EN 55032:2015
Test Method:	EN 55032:2015
Frequency Range:	30MHz to 1GHz
Measurement Distance:	10m
Limit:	
30MHz-230MHz	30 dB( $\mu$ V/m) quasi-peak
230MHz-1GHz	37 dB( $\mu$ V/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to 1000MHz

### 6.2.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 54 % RH Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case:

- a: DC5V full output mode, keep EUT working with full load.
- b: DC9V full output mode, keep EUT working with full load.
- c: DC12V full output mode, keep EUT working with full load.
- d: Idle mode.

The worst case for final test: b: DC9V full output mode, keep EUT working with full load.


### 6.2.2 Test Setup Diagram



### 6.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.


Mode:b; Polarization:Horizontal



Condition: 10m HORIZONTAL  
EUT : 12088PS  
Test Mode: b

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	42.45	6.80	13.11	32.45	26.91	14.37	30.00	-15.63
2	59.65	7.00	12.03	32.45	26.92	13.50	30.00	-16.50
3	148.96	7.45	13.34	32.43	27.87	16.23	30.00	-13.77
4	599.32	8.90	18.70	32.28	29.38	24.70	37.00	-12.30
5	701.76	9.16	20.14	32.27	27.80	24.83	37.00	-12.17
6 pp	968.93	9.60	22.79	30.85	26.59	28.13	37.00	-8.87

Mode:b; Polarization:Vertical



Condition: 10m VERTICAL

EUT : 12088PS

Test Mode: b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	43.51	6.80	13.02	32.45	30.35	17.72	30.00	-12.28
2 pp	58.82	7.00	12.09	32.44	35.69	22.34	30.00	-7.66
3	162.04	7.50	13.19	32.44	31.85	20.10	30.00	-9.90
4	206.40	7.63	9.44	32.45	35.21	19.83	30.00	-10.17
5	460.73	8.45	16.30	32.30	28.60	21.05	37.00	-15.95
6	760.70	9.20	20.90	32.26	27.81	25.65	37.00	-11.35





### **6.3 Harmonic Current Emission**

Test Requirement: EN 61000-3-2:2014

Test Method: EN 61000-3-2:2014

Frequency Range: 100Hz to 2kHz

There is no need for Harmonics test to be performed on this product (rated power is less than 75W) in accordance with EN 61000-3-2:2014.

For further details, please refer to Clause 7 of EN 61000-3-2 which states:

"For the following categories of equipment, limits are not specified in this standard.- equipment with a rated power of 75W or less, other than lighting equipment."

## 6.4 Voltage Fluctuations and Flicker

Test Requirement: EN 61000-3-3:2013

Test Method: EN 61000-3-3:2013

### 6.4.1 E.U.T. Operation

Operating Environment:


Temperature: 24.7 °C Humidity: 45.5 % RH Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case:

- a: DC5V full output mode, keep EUT working with full load.
- b: DC9V full output mode, keep EUT working with full load.
- c: DC12V full output mode, keep EUT working with full load.
- d: Idle mode.

The worst case for final test: c: DC12V full output mode, keep EUT working with full load.

### 6.4.2 Test Setup Diagram



### 6.4.3 Measurement Data




Mode:c

Test Result: Pass


Status: Test Completed

#### Pst<sub>i</sub> and limit line

#### European Limits



#### Plt and limit line



#### Parameter values recorded during the test:

Vrms at the end of test (Volt): 230.07

Highest dt (%): 0.00

Time(mS) > dt: 0.0

Highest dc (%): 0.00

Highest dmax (%): 0.00

Highest Pst (10 min. period): 0.160

Test limit (%): 3.30 Pass

Test limit (mS): 500.0 Pass

Test limit (%): 3.30 Pass

Test limit (%): 4.00 Pass

Test limit: 1.000 Pass

## **7 Immunity Test Results**


### **7.1 Performance Criteria Description in EN 55024:2010 +A1:2015**

<b>Criterion A</b>	The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
<b>Criterion B</b>	<p>After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.</p> <p>During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test.</p> <p>If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
<b>Criterion C</b>	<p>Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions.</p> <p>Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>

## 7.2 Electrostatic Discharge

Test Requirement: EN 55024:2010 +A1:2015  
 Test Method: EN 61000-4-2:2009  
 Performance Criterion: B  
 Discharge Impedance: 330Ω/150pF  
 Number of Discharge: Minimum of four test points (a minimum of 50 discharges at each point)  
 Discharge Mode: Single Discharge  
 Discharge Period: 1 second minimum

### 7.2.1 Test Setup Diagram



### 7.2.2 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 46 % RH Atmospheric Pressure: 1020 mbar

Test mode:  
 a: DC5V full output mode, keep EUT working with full load.  
 b: DC9V full output mode, keep EUT working with full load.  
 c: DC12V full output mode, keep EUT working with full load.  
 d: Idle mode.

### 7.2.3 Test Results:

Observations: Test Point:  
 1. All insulated enclosure and seams.  
 2. All accessible metal parts of the enclosure.  
 3. All side

Discharge type	Level (kV)	Polarity	Test Point	Result / Observations
Air Discharge	2,4,8	+	1	A
Air Discharge	2,4,8	-	1	A
Contact Discharge	4	+	2	A
Contact Discharge	4	-	2	A
Horizontal Coupling	4	+	3	A
Horizontal Coupling	4	-	3	A
Vertical Coupling	4	+	3	A
Vertical Coupling	4	-	3	A


### Results:

A: No degradation in the performance of the EUT was observed.

### 7.3 Radiated Immunity (80MHz-1GHz)

Test Requirement: EN 55024:2010 +A1:2015  
 Test Method: EN 61000-4-3:2006 +A1:2008+A2:2010  
 Performance Criterion: A  
 Frequency Range: 80MHz to 1GHz  
 Antenna Polarisation: Vertical and Horizontal  
 Modulation: 1kHz,80% Amp. Mod,1% increment

#### 7.3.1 Test Setup Diagram



#### 7.3.2 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 58 % RH Atmospheric Pressure: 1015 mbar

Test mode:  
 a: DC5V full output mode, keep EUT working with full load.  
 b: DC9V full output mode, keep EUT working with full load.  
 c: DC12V full output mode, keep EUT working with full load.  
 d: Idle mode.

#### 7.3.3 Test Results:

Frequency	Level (V/m)	EUT Face	Dwell time	Result / Observations
80MHz-1GHz	3	Front	2s	A
80MHz-1GHz	3	Back	2s	A
80MHz-1GHz	3	Left	2s	A
80MHz-1GHz	3	Right	2s	A
80MHz-1GHz	3	Top	2s	A
80MHz-1GHz	3	Underside	2s	A


#### Results:

A: No degradation in the performance of the EUT was observed.

## 7.4 Electrical Fast Transients/Burst at Power Port

Test Requirement: EN 55024:2010 +A1:2015  
 Test Method: EN 61000-4-4:2012  
 Performance Criterion: B  
 Repetition Frequency: 5kHz  
 Burst Period: 300ms  
 Test Duration: 2 minute per level & polarity

### 7.4.1 Test Setup Diagram



### 7.4.2 E.U.T. Operation

Operating Environment:

Temperature: 24.7 °C Humidity: 45.4 % RH Atmospheric Pressure: 1005 mbar

Test mode:  
 a: DC5V full output mode, keep EUT working with full load.  
 b: DC9V full output mode, keep EUT working with full load.  
 c: DC12V full output mode, keep EUT working with full load.  
 d: Idle mode.

### 7.4.3 Test Results:

Test Line	Level (kV)	Polarity	CDN/Clamp	Result / Observations
AC power port	1	+	CDN	A
AC power port	1	-	CDN	A


#### Results:

A: No degradation in the performance of the EUT was observed.

## 7.5 Surge at Power Port

Test Requirement: EN 55024:2010 +A1:2015  
 Test Method: EN 61000-4-5:2014  
 Performance Criterion: B  
 Interval: 60s between each surge  
 No. of surges: 5 positive, 5 negative at 0°, 90°, 180°, 270°.

### 7.5.1 Test Setup Diagram



### 7.5.2 E.U.T. Operation

Operating Environment:

Temperature: 24.7 °C Humidity: 45.5 % RH Atmospheric Pressure: 1005 mbar

Test mode:  
 a: DC5V full output mode, keep EUT working with full load.  
 b: DC9V full output mode, keep EUT working with full load.  
 c: DC12V full output mode, keep EUT working with full load.  
 d: Idle mode.

### 7.5.3 Test Results:

Test Line	Level (kV)	Polarity	Phase (deg)	Result / Observations
L-N	1	+	0°	A
L-N	1	-	0°	A
L-N	1	+	90°	A
L-N	1	-	90°	A
L-N	1	+	180°	A
L-N	1	-	180°	A
L-N	1	+	270°	A
L-N	1	-	270°	A

### Results:


A: No degradation in the performance of the EUT was observed.



## 7.6 Conducted Immunity at Power Port (150kHz-80MHz)

Test Requirement: EN 55024:2010 +A1:2015  
Test Method: EN 61000-4-6:2014  
Performance Criterion: A  
Frequency Range: 0.15MHz to 80MHz  
Modulation: 80%, 1kHz Amplitude Modulation  
Step Size: 1%

### 7.6.1 Test Setup Diagram



### 7.6.2 E.U.T. Operation

Operating Environment:  
Temperature: 24.7 °C Humidity: 45.4 % RH Atmospheric Pressure: 1005 mbar  
Test mode:  
a: DC5V full output mode, keep EUT working with full load.  
b: DC9V full output mode, keep EUT working with full load.  
c: DC12V full output mode, keep EUT working with full load.  
d: Idle mode.

### 7.6.3 Test Results:

Cable port	Level (Vrms)	CDN/Clamp	Dwell time	Result / Observations
AC power port	3	CDN	2s	A

#### Results:

A: No degradation in the performance of the EUT was observed.

## 7.7 Voltage Dips and Interruptions

Test Requirement: EN 55024:2010 +A1:2015


Test Method: EN 61000-4-11:2004

Performance Criterion: 0% of UT (Supply Voltage) for 0.5 Periods:B; 0% of UT for 250 Periods:C;  
 70 % of UT for 25 Periods:C

No. of Dips / Interruptions: 3 per Level

Time between dropout 10s

### 7.7.1 Test Setup Diagram



### 7.7.2 E.U.T. Operation

Operating Environment:

Temperature: 24.7 °C Humidity: 45.4 % RH Atmospheric Pressure: 1005 mbar

Test mode:  
 a: DC5V full output mode, keep EUT working with full load.  
 b: DC9V full output mode, keep EUT working with full load.  
 c: DC12V full output mode, keep EUT working with full load.  
 d: Idle mode.

### 7.7.3 Test Results:

Level % UT	Phase (deg)	Duration	No. of Dips / Interruptions	Result / Observations
0	0°	0.5 Cycles	3	A
0	180°	0.5 Cycles	3	A
0	0°	250 Cycles	3	C
0	180°	250 Cycles	3	C
70	0°	25 Cycles	3	A
70	180°	25 Cycles	3	A

### Results:

A: No degradation in the performance of the EUT was observed.


C: The EUT stops working during the test, but can recover automatically after the test.

## 8 Photographs


### 8.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) Test Setup



### 8.2 Radiated Emissions (30MHz-1GHz) Test Setup



### 8.3 Voltage Fluctuations and Flicker Test Setup




### 8.4 Electrostatic Discharge Test Setup





### 8.5 Radiated Immunity (80MHz-1GHz) Test Setup




### 8.6 Electrical Fast Transients/Burst at Power Port Test Setup



## 8.7 Surge at Power Port Test Setup



## 8.8 Conducted Immunity at Power Port (150kHz-80MHz) Test Setup




## 8.9 Voltage Dips and Interruptions Test Setup







### 8.10 EUT Constructional Details (External and Internal Photos)









- End of the Report -